



TorqueConqueror VTC3-1500 Power Tongs

SPECIFICATIONS:

Range: Sucker Rods Sizes:	5/8", 3/4", 7/8", 1"
Rated low gear torque:	1476ft.lbs, High Gear speed: 46 RPM
Rated high gear torque:	590ft.lbs, High Gear speed: 120 RPM
Dimension of opening:	Main Tongs: 2.6", Back-up Tong: 2.6"
Travel mass:	Main Tong: 396bs, Back-up Tong: 195lbsg
Rated system pressure:	1590psi
Max. oil supply:	21 gpm
Overall Dimensions:	L×W×H: 25.6?×15?×19.7? (650×380×500mm)



FEATURES:

- Open Face Style, Compact in Size, Low Noise, Ideal for Sucker Rods Handling in Workover Operation, Available in Style A and B
- Interchangeable Parts for Main Tong and Back-up Tongs for Easy Maintenance,
- Easy-Grab Design Allowing Proper Jaw Engagement at Any Position When Handling All Four Sizes (5/8", 3/4", 7/8", 1") of Sucker Rods Without the Need to Change Any Parts or Alignment
- Automatic Open-Close Design Providing Safety
- Dual Function Relief Valve Effectively Controls Make up and Break-out Torque and Serves as Overload Protection



VTC3-1500A



VTC3-1500B

DISTRIBUTED BY:

MANUFACTURER:
VJF INTERNATIONAL INC
Phone: 604 376 7919
Fax: 604 301 9918
E-mail: sales@vjfi.com

Note: Product Information as Specified herewith is kept accurate up-to-date at time of its printing, and are for reference only. End user is asked to use Users Instruction Manual shipped with each unit. Product info provided in this flyer is subject to change without notice.

