



TorqueConqueror VTC5-4000 Power Tongs

SPECIFICATIONS:

Range: Main Tong:	2-7/8", 3-1/2", 4-1/2"
Back-up Tong:	3-1/2" to 5.57"
Rated low gear torque:	4428ft.lbs, Top speed: 20 RPM
Rated high gear torque:	1107ft.lbs, Top speed: 80 RPM
Dimension of opening:	Main Tongs: 4.72", Back-up Tong: 5-3/8"
Travel mass:	Main Tong: 396bs, Back-up Tong: 195lbs
Rated system pressure:	1590psi
Max. oil supply:	26 gpm
Overall Dimensions:	L×W×H: 35.4?×21.7?×26.8? (900×550×680mm)

FEATURES:

- Open Face Style, Compact in Size, Low Noise, Ideal for Workover Operation
- Synchronized Movement of Main Tongs and Back-Up Tongs,
- Curved Track Internal Roller Movement Provides Safety and Reliability
- Steering Mechanism on Top of Tong Heads Providing Easy Access and Convenience for Maintenance
- Overload Protection System Built-in
- Spring / Hydraulic Hanger System Allows Convenient Adjustment of the Unit to Suit Operation Requirement
- Automatic Torque Control System Available to Pre-set Torque Value.
- Optional Torque-Matics Computerized Recorder /Alarm Systems (Sold as optional item)



DISTRIBUTED BY:

MANUFACTURER:
VJF INTERNATIONAL INC
Phone: 604 376 7919
Fax: 604 301 9918
E-mail: sales@vjfi.com

Note: Product Information as Specified herewith is kept accurate up-to-date at time of its printing, and are for reference only. End user is asked to use Users Instruction Manual shipped with each unit. Product info provided in this flyer is subject to change without notice.

