



TorqueConqueror VTC6-9000 Power Tongs

SPECIFICATIONS:

Range: Tubing:	2-7/8", 3-1/2", 4-1/2"
Small drill Pipe:	2-7/8", 3-1/2"
Casing:	5", 5-1/2"
Rated low gear torque:	9960ft.lbs, Top speed: 14.5r/min
Rated second-low gear torque:	5830ft.lbs, Top speed: 25r/min
Rated second-high gear torque:	3395ft.lbs, Top speed: 43r/min
Rated high gear torque:	1990ft.lbs, Top speed: 75r/min
Max. instantaneous torque:	11070ft.lbs
Dimension of opening:	Main tongs: 5.9?; Backup tongs: 6.3?
Travel mass:	1080lbs
Rated system pressure:	1740psi
Max. oil supply:	34gpm
Overall Dimensions:	L×W×H: 42?×22.9?×29.5? (1068×582×750mm)

FEATURES:

- Interchangeable Tong Dies for all pipe sizes; Curved Surface Roller Climbing System
- Simple and Reliable Rotation Control for Main and Back-up Tongs
- Broad Torque and RPM Range Achievement
- Overload Protection System Built in Manual Reversing Valves
- Spring / Hydraulic Hanger System Allows Convenient Adjustment of the Unit to Suit Operation Requirement
- Automatic Torque Control System Available to Pre-set Torque Value.
- Optional Torque-Matics Computerized Recorder /Alarm Systems (Sold as optional item)



DISTRIBUTED BY:

MANUFACTURER:
VJF INTERNATIONAL INC
Phone: 604 376 7919
Fax: 604 301 9918
E-mail: sales@vjfi.com

Note: Product Information as Specified herewith is kept accurate up-to-date at time of its printing, and are for reference only. End user is asked to use Users Instruction Manual shipped with each unit. Product info provided in this flyer is subject to change without notice.

