



Torque-Matics Recorder VTM-WN-98-1 & VTM-WNZK-2002

SPECIFICATIONS:

Torque Control Range:	0—6.50 KNM
Torque Alarm Reading:	< 10NM
Signal Delay:	< 20MS
Relief Valve Lapse:	1 second to 60 seconds (set at choice of user)
Ambient Temperature:	- 20 Deg C— + 60 deg C
Power Supply:	220V/110V, 50Hz/60Hz (also work with 24VDC)
Memory:	4000 Torque Values

FEATURES:

- Great Companion to TorqueConqueror Power Tongs for Worker History Management, Record keeping for as long as 10 years
- Fully Computerized, Fully Automatic, Easy to Install and Free of Maintenance
- Capability to Automatically Store, Memorize, and Print Torque Values, to ensure Torque Consistency for Each Connections
- Available in One Piece Cabinet Style (VTM-VTM-WNZK-2002) and Split Type Style (VTM-WN-98-1) to Customer Preference



DISTRIBUTED BY:

MANUFACTURER:
VJF INTERNATIONAL INC
Phone: 604 376 7919
Fax: 604 301 9918
E-mail: sales@vjfi.com

Note: Product Information as Specified herewith is kept accurate up-to-date at time of its printing, and are for reference only. End user is asked to use Users Instruction Manual shipped with each unit. Product info provided in this flyer is subject to change without notice.

